

## CONTROL SEVERAL CHARGING POINTS ON LINE

Our evBusiness charger (E-30) is designed for businesses that need to make charging profitable and manage several charging points at the same time through the online platform.

The OCPP protocol system allows the management of payments and recharge points through the APP or through the backend



## **MAIN FEATURES**

These are the most important features of our advertised charger







**DURABLE** 



PROTOCOLO
OCPP 1.6



SUITABLE FOR OUTDOOR USE (IP54)



**FAST CHARGING** 

## **SPECIFICATIONS**

Input		
Phases	1 phase + neutral+ PE	3 phases + netural+ PE
Voltage	230V±10%	400V±10%
Frequency	50Hz	50Hz
Output		
Voltage	230V±10%	400V±10%
Current	32A	32A
Power	7.4 kW	22 kW
Front Casing		
Structure	Plastic PC940	Galvanised steel
Material	Temper glass	
Installation Method	Pedestal/Wall	
Charging	Charging socket type 2	
LED Indicator	Green/Yellow/Red depending on status 2.7"	
LCD RFID	Indicates charging data	
Display	Yes, Mifare ISO/IEC 14443 A	
Power mode	Switch on/off via RFID and APP	
Energy Meter	MID	
RCD	certified Type	
Communication	A+ 6mA DC	
WiFi		Yes
Ethernet		Optional
3G/4G	Optional	
OCPP	OCPP 1.6 Json (OCPP 2.0 optional)	
Communication Protocol	OCPP 1.6 (JSON)	
REID	Yes	
App		Yes
		103
Environment		20 50 6
Temperature	- 30~ + 50 C	
Humidity	5%~95%, without condensation.	
Altitude	<2000M	
Degree of protection	IP54	
Environment	Indoor/Outdoor	
Cooling		Natural cooling
Safety		
	Over-voltage / under-voltage protection, over-charging protection, short-circuit protection, protection against current leakage	
Protection against	current, earthing protection, over-voltage protection,	
	over-temperature / under-temperature protection	
		e / under-temperature protection
Impact protection		IKO80
Standard certification	EN/IEC 61851-1:2017, EN/IEC 61851-21-2:2018	
Standard certification		CE
Dimensions		
Product dimensions	356 x 221 x 136 mm (H*W*D)	356 x 221 x 136 mm (H*W*D)
Box dimensions	490 x 330 x 210 mm (L*W*H)	490 x 330 x 210 mm (L*W*H)
Net weight	3.4 kg	11 kg
Gross weight:	4.2 kg	12 kg